

Metal enclosures **BGUK 40**



Picture shows BGUK 30/2

Advantages

Integrated rail system for the installation of different product sizes (BGUK 30 - BGUK 60)
Excellent corrosion protection and high abrasion resistance through powder-coated surface RAL 5008
Ventilation openings for optimized cooling
Faceplate without cooling fins for individual connection options (BGUK 10 - 60)
Integrated crane eyes

Applications

Universal metal enclosure with cooling fins for degree of protection IP20/IP23

Approvals



Metal enclosures BGUK 40

Type		BGUK 40
Electrical data	Operating data	
	Enclosure suitable for protection index	IP 23
	For power (single-phase)*	10,000 VA
	For power (three-phase)*	6,300 VA
	Max. Power loss (at 40 °C ambient temperature)	340 W
Notes	The indicated power is a guideline. Deviations may occur depending on the version of the transformer.	
*		
Order numbers		
Order Number		BGUK 40

Type		BGUK 40
Mechanical data	Terminal and mounting	
	Floor mounting	Yes
	Wall mounting	Yes
	Cable glanding type	2x M 32
	Cable glanding Ø	13 - 17 mm
Measures and weights		
Effective inside dimension (W)	455 mm	
Effective inside dimension (D)	275 mm	
Effective inside dimension (H)	425 mm	
Fixing hole Ø	11 x 14 mm	
Weight	22.0 kg	

